Fujitsu recommends Windows® 7.

Data Sheet
Fujitsu ESPRIMO P2560 Desktop PC

Your Immediately Available Office PC

The Fujitsu ESPRIMO P2560 is designed for price-conscious customers and is equipped with state-of-the-art standard Intel® technology. This system meets every office requirement - especially those typical for small and medium-sized businesses. Fujitsu ESPRIMO P2560 is available from your dealer at all times and therefore an ideal choice once the decision to purchase has been taken.

Attractive price
PC for the day-to-day challenges of office life
- Proven Intel® technology

Designed and engineered in Germany
Outstanding quality and stable functions based on German production standards
- The development, production and function tests are all under one roof in Germany

Immediate availability
Short waiting times once purchase decision has been taken.
- Preferred versions available on-site

Fujitsu recommends Windows® 7.

Components

Processor	Intel® Pentium® processor E6700 (2 Cores / 2 Threads, 3.20 GHz, 2 MB)
	Intel® Pentium® processor E6600 (2 Cores / 2 Threads, 3.06 GHz, 2 MB, 1066 MHz)
	Intel® Pentium® processor E5800 (2 Cores / 2 Threads, 3.2 GHz, 2 MB, 800 MHz)
	Intel® Celeron® processor E3400 (2 Cores / 2 Threads, 2.6 GHz, 1 MB, 800 MHz)
Operating systems	
Operating system	Genuine Windows® 7 Starter (EM) 32-bit Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Operating system compatible	openSUSE Linux Genuine Windows Vista® Genuine Windows® XP
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	1 GB (1 module(s) 1 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM
	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM
Hard disk drives (internal)	HDD SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
	HDD SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
	HDD SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T.
	HDD SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
Graphics add on cards (optional)	NVIDIA® GeForce® 405 display port full height
	DVI Extension Adapter
	DVI-D + DisplayPort Extension Adapter
	ATI Radeon® HD 5450, 512 MB
Drives (optional)	DVD-ROM
	DVD Super Multi
	MultiCard Reader 20in1, USB 2.0, 3.5-Inch
Interface add on cards/components (optional)	
	WLAN III, 802.11g/Draft-n (Windows only)
	USB 3.0 PCIe x1
	Parallel Interface
	Modem adapter kit (EU)
	Modem 56k incl. RJ11 modem cable
	Gigabit Ethernet PCIe x1, DS
	Gigabit Ethernet PCIe x1
	FireWire PCI-Card IEEE1394
	Dual serial card PCI
Base unit	ESPRIMO P2560
Mainboard	
Mainboard type	D3041
Formfactor	reduced ATX
Chipset	Intel® G41
Processor socket	LGA 775

Mainboard	
Processor quantity maximum	1
System bus (FSB / HT / QPI)	up to 1333 MHz
Memory slots	2 DIMM (DDR3)
Supported capacity RAM (max.)	8 GB
Memory frequency	1066 MHz
Memory notes	For combinations of 32-bit operating systems with 3 GB of memory or above the accessible memory may be reduced to 3 GB or less (depending on system configuration). Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same
LAN	10/100/1000 MBit/s Realtek RTL8111DL
BIOS version	Phoenix 6.0
BIOS features	BIOS based on Phoenix SecureCore Recovery BIOS
Audio codec	Realtek ALC663
Audio features	High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	4
Controller functions	Serial ATA II 3 GBit
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	8
USB front	2
USB rear	4
USB internal	2
VGA	1
DisplayPort	1 (optional)
DVI	1 (optional)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
Interface Module notes	Anytime USB charge functionality
Input device / components	
	Optical USB wheel mouse Keyboard
Drive bays	
Drive bays total	5
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2
Slots	
PCI-Express x16	1 x (210 mm) Full height
PCI-Express x1	1 Full height
PCI (32-bit / 33 MHz)	2 x (170/ 220 mm) Full height
Graphics on board	
Graphics brand name	Intel® GMA 4500

Graphics on board	
Shared video memory	up to 1759 MB
Refresh rate 1024 x 768 (recommended / max.)	85 Hz / -
Refresh rate 1280 x 1024 (recommended / max.)	85 Hz / -
Refresh rate 1600 x 1200 (recommended / max.)	85 Hz / -
TFT resolution (VGA)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
Graphics features	DirectX 10 HDCP support OpenGL® 2.0
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
Electrical values	
	0-Watt mode with hard-off switch
Power supply input	200 - 240 V ~1,5A
Rated voltage range	200 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	200 V - 240 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	300 W
Monitor outlet	No
Power consumption	
Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=2a51d0d3-000c-47a3-ae8a-19c00547e984
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise for standard configuration (HDD, ODD, FDD)	
Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™2 Quad Q8300
Noise Operation mode 1: ODD load (Blue angel requirement)	5.1 B / 36 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	4.5 B / 30 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	5.1 B / 36 dB(A)
Noise Operation mode 4: High load	5.2 B / 37 dB(A)
Noise Operation mode 5: Office applications	4.7 B / 32 dB(A)
Idle mode (Blue Angel requirement)	4.4 B / 29 dB(A)
Noise notes / description	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	175 x 425 x 353 mm
Operating position	Vertical
Weight	approx. 11 kg

Fujitsu recommends Windows® 7.

Dimensions / Weight / Environmental	
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	15 - 35°C
Compliance	
Product	ESPRIMO P2560
Model	MI4W-D3041
Europe	CE
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/
Additional Software	
Additional software (preinstalled)	Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) 60 days version
Additional software (optional)	Drivers & Utilities DVD (DUDVD) Recovery DVD for Windows® Nero 9 Essentials XL
Compatibility (references)	
	DMI 2.0 PC 2001 WMI 1.5 USB 2.0 SMBIOS
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode)
DeskView components	WoL (Wake on LAN)
Security	
System protection	Kensington Lock support Eye for padlock
Audit proof protection	Boot sector virus protection Control of external interfaces
Access protection	User and supervisor BIOS password Optional: Access protection via external SmartCard reader
Packaging information	
Packaging dimension	500x290x540 mm
Max. quantity / pallet	24
Material - Weight (g) Carton	1270 g
Material - Weight (g) EPS / PS	210 g
Material - Weight (g) PE	appr. 60 g
Packaging notes	printed user documentation is bleached in chlorine free process
Warranty	
Service level	(depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	3 years
Service Weblink	http://ts.fujitsu.com/Supportservice

More information

Fujitsu platform solutions

In addition to Fujitsu ESPRIMO P2560, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO P2560, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
http://ts.fujitsu.com/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact
FUJITSU Technology Solutions
Website: http://ts.fujitsu.com
2011-10-28 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions